

MODEL
FD6700S/FD6700S-T
Peak Output
5500W
Rated Output
4500W

Clean Power, Ideal for sensitive electronics less than 5% THD, only for 50Hz Generator

SPECIFICATIONS

ENGINE	BFT	
Displacement (cc)	418	
Engine Type	Single cylinder, 4-Stroke, OHV, Air Cooled	
Run Time @ 50% Load	7.5h	7h
Low Oil Sensor	Yes	

CONTROL PANEL	"M" Panel Type	
Outlets	2X 16A 250V Blue Schuko(IP44), 1 X CEE Socket 230V 32A (industrial type)	2X 120V 20A Duplex Outlets, 1X 120/ 240V AC 30A Twist-lock (NEMA L14-30)
Frequency	50Hz	60Hz
AVR	Yes	
3 in 1 Meter [Volts/ Frequency/ Hours]	Yes	Yes
Hour Meter(LCD)	N/A	Yes
Circuit Breakers	Yes	
Rubber Outlet Dust Covers	N/A	

OVERALL DESIGN

Frame Style	N/A
Frame Finish	N/A
Wheel & Tire Type	4" x 4 Chrome Plated Wheel (F150 Style) Never Flat PU Foam Tire
Fuel Tank Size (L / Gal.)	15 /4

OTHER GENERATOR FEATURES

Fuel Gauge	Yes	
Starter Type	Electric	
Battery Type	12V 14Ah	
Battery Included	Yes	Yes

PACKAGING DETAILS

Carton Type	Wood Box
Gross Weight (kg / lbs.)	167 / 368.2

FRIEGHT QTY (with Pallet)

40HQ	144
MOQ	Two 40ft Containers

CERTIFICATIONS

CE-EMC	Yes	N/A
EPA3	N/A	N/A
CARB	N/A	N/A
CSA	N/A	N/A
EU-II	N/A	N/A